



Falamat forte

Cleaner for use in automatic cleaning machines,
grease and soiling solvent

Packaging	Art.-No.	per Box	per Palett
10 l PE-Canister	9383	-	40

Properties:

Falamat forte is an alkaline grease and dirt remover for use in automatic cleaning machines (scrubber dryers or roller brush machines) for maintenance and intermediate cleaning. Particularly suitable for soiling that cannot be removed by neutral cleaners. Thoroughly and gently cleans all types of floor coverings, such as PVC, linoleum, rubber knobs, epoxy resin floors, natural stone, artificial stone, ceramic tiles. Cannot be used on wax or acrylic floor polishes / films. Low foaming, dries clear and streak-free. Can also be used in the manual wet wiping process.

Field of Application:

For use in automatic cleaning machines (scrubber dryer or brush roller machine). maintenance or intensive cleaning of all waterproof and alkali-resistant

Application:

For daily maintenance cleaning, equip the machine with a diluted cleaning solution and treat floor covering using the automatic machine. Manual processing: work in a two-stage wiping process. Intensive cleaning: Apply cleaning solution onto the floor surface, allow to act (5-10 min.), scrub and then soak up the dirt solution, rinse with clear water.

Dosage:


Automatic machine cleaning: 25 - 50 ml to 10 l water (dilution 1:200 - 1:400).
Manual maintenance cleaning: 150 - 200 ml to 10 l water (dilution 1:50 - 1:75).

Ingredients:

<5% anionic surfactants, <5% non-ionic surfactants, Methylchloroisothiazolinone, Methylisothiazolinone, perfumes.

Productcode: GU 80

This product is intended for commercial use only. Safety data sheet available on request or at www.fala.de. For safety instructions pay attention to product label or safety data sheet.




The information contained herein corresponds at the time of publication to our best present-day knowledge. It is the responsibility of the user to ensure that the product is suitable for the intended application.




Automatic processing
by means of
machines



Manual processing
by wiping



Automatic cleaning:
Dilution with water
1:200 to 1:400



Maintenance cleaning:
Dilution with water
1:50 to 1:75